

BE3010P-KE

Features:

- Performance 3000Psi / 15l/min.
- Kohler Air Cooled 10Hp Diesel 15LD440
- Belt Drive @ 1400Rpm
- Optional Trailer Pack
- ****Battery not included****



Optional Wheel Kit AHSK5



Optional Trailer Pack



BE3010P-KE

WS200.15 Blitz Hot

WS200.15 Blitz Hot

Features:

- Performance 3000Psi / 15l/min.
- Kohler Air Cooled 10Hp Diesel 15LD440 (with 12v Electric Start & 30 Amp Alternator)
- Interpump Piston Pump c/w gauge, safety valve & filters
- Gearbox Transmission at 1450Rpm & Automatic Accelerator
- 12V Vertical Boiler Assembly with Stainless Steel Casing
- Galvanised steel chassis with built in diesel fuel tank
- Anti Vibration Plate for smoother running
- 12V control panel with 12V auxiliary socket
- Complete with gun, lance & 10 metres of hose
- ****Battery not included****



WS200.15 Hot Skid Silent

MUNICIPAL SPECIFICATION - Ideal for van mounted, early morning cleaning - literally whisper quiet

Features:

- Performance 3000Psi / 15l/min.
- Kohler Water Cooled 17Hp Twin Cylinder Diesel (with 12v Electric Start & 30 Amp Alternator)
- Interpump Piston Pump c/w gauge, safety valve & filters
- Joined with Elastic Joint @ 1800 Rpm
- 12V Vertical Boiler Assembly with Stainless Steel Casing
- Galvanised steel chassis with built in diesel fuel tank
- Anti Vibration Plate for smoother running
- 12V control panel with 12V auxiliary socket
- Complete with gun, lance & 10 metres of hose
- ****Battery not included****
- Silent Pack Options
 - Standard machines generate 78 dba @ 7 metres
 - Silent Pack version reduces noise to 63 dba @ 7 metres
 - Ask for our video - the only noise is the water



*** Silent pack displayed. Standard machine is open with no stainless cover

Hot Water Diesel



DIESEL ENGINE / DIESEL BURNER

WS330.21 Hot Skid

WS330.21 Hot skid

Features:

- Performance 5000Psi / 21l/min.
- Kohler Water Cooled 30Hp Three Cylinder Diesel (with 12v Electric Start & 30 Amp Alternator)
- Interpump Piston Pump c/w gauge, safety valve & filters
- Direct Transmission @ 1800 Rpm
- Automatic accelerator
- 12V DC Vertical Boiler Assembly with Stainless Casing
Boiler flow rate 51.816 kcal/h
- Coil upgraded to 3mm steel wall
- Galvanised steel chassis with built in diesel fuel tank
- Lifting Hook supplied standard
- Adjustable feet
- Anti Vibration Plate for smoother running
- 12V control panel with 12V auxiliary socket
- Complete with gun, lance & 10 metres of hose
- ****Battery not included****
- Silent Pack Option coming soon, although water cooled diesel machines are generally quiet



MINING SPECIFICATION
The model everybody has asked for

Models						
MODEL	3010P-KE	WS200.15 Blitz	WS150.21 Blitz	WS200.15 Hot Skid	WS150.21 Hot Skid	WS330.21 Hot Skid
Production Number	SK30004-DH	93100312	93100313	93100350	93100355	93100370
PERFORMANCE	Diesel Air Cooled	Diesel Air Cooled	Diesel Air Cooled	Diesel Water Cooled	Diesel Water Cooled	Diesel Water Cooled
Water Pressure (Psi)	3000 Psi	3000 Psi	2200 Psi	3000 Psi	2200 Psi	5000 Psi
Water Flow Rate	15 l/min.	15 l/min.	21 l/min.	15 l/min.	21 l/min.	21 l/min.
Max Outlet Water Temp.	85°C	140°C	140°C	40→150°C	40→150°C	40→150°C
Engine - Horsepower	10Hp	10Hp	10Hp	17Hp Twin Cylinder	17Hp Twin Cylinder	40Hp Three Cylinder
- Model	Kohler USA	Kohler Italy	Kohler Italy	Kohler FOCS	Kohler FOCS	Kohler FOCS
- Start	Electric	Electric	Electric	Electric	Electric	Electric
- Type	Kohler USA	15LD225	15LD225	LDW702	LDW702	LDW1602
- Cooling	Air	Air	Air	Water 2 Cyl	Water 2 Cyl	Water 3 Cyl
Fuel Tank				75 Litres	75 Litres	75 Litres
Machine Noise Level				78db @ 7 metres	78db @ 7 metres	78db @ 7 metres
Pump - Type	AR	Interpump	Interpump	Interpump	Interpump	AR
- Model		WS151		W921		SXWA5.5G50
- Speed	1400 Rpm Belt Drive	1450 Rpm	1450 Rpm Belt Drive	1800 Rpm Direct	1800 Rpm Direct	1800 Rpm Direct
- Unloader Valve	External	External	External	External	External	External
Burner	C2 Burner	12Volt	12Volt	12Volt	12Volt	12Volt
Weight - Dead		200 Kg	200 Kg	300 Kg	300 Kg	
Dimensions		W1460xL890xH10	W1460xL890xH1	W700xL1200xH1000	W700xL1200xH1000	
List	\$9,999 A	\$poa	\$poa	\$poa	\$poa	\$poa



Silent Pack Version
63 dba @ 7 Metres
WS200.15 Hot Skid Silent
Spec: 93100341

Silent Pack Version
63 dba @ 7 Metres
WS150.21 Hot Skid Silent
Spec: 931003XX

