

X-Star and KL & KS Series - Buy the right machine the first time.
The BAR BLUE series are Italian manufactured Pressure Cleaners made especially for the domestic buyer looking for quality.

Understand the industry code for budget vs quality domestic machines:
Budget: Rust proof (plastic) pump / Universal electric motor
Quality: Axial Pump (metal) pump / Induction electric motor

Features include:

- Comet Italian Axial Pump
- Italian induction electric motor
- Plenty of weight, but very easy to wheel around
- Built in accessory holder
- KL1600 features professional rated accessories
- Supplied ready to work with gun, lance, hose, detergent injection, turbo & vario nozzles



Supplied ready to go



X-Star



KL1400



KL1600A



Optional Accessories		
 Hose Extension \$poa	 Rotating Brush \$poa	 Fixed Brush \$poa
 Water Inlet Filter \$poa	 Drain Cleaner \$poa	 Floor Cleaner \$poa

Accessories X-star / KL1400	Accessories KL1600/KT1800/K200
 Gun (with M22 end) \$poa	 Gun (with M22 end) \$poa
 Lance c/w Turbo & Variable Nozzles \$poa	 Lance c/w Variable Nozzle \$poa
 Lance c/w Turbo Nozzle \$poa	 Lance c/w Turbo Nozzle \$poa
 Hose \$poa	 Hose \$poa

Electric Pressure Cleaners

2800 Rpm Semi Professional



COMET ITALY BLUE SERIES

KT Series - Comet Italy have launched the new generation KT Series.

Designed for the premium home buyer or medium duty professional user, the KT gives our long successful KS1700 and KA2500 models a fresh look

K200 Series - Comet Italy have designed this series especially for BAR

Featuring the same rugged framework and Hose Reel option as the K250 Industrial series, these models also have a 10% longer design life than the KT Series,



KT1800



K200

2800 Rpm ELECTRIC							
	DOMESTIC			SEMI-PROFESSIONAL			
Model	X-star	KL1400	KL1600A	KT1800	KT1900	K200 9/120C	K200 9/120E
Pressure	1750	2030	2175	2175	2300	2030	2030
Flow	6	6.8	8	9	10	9	9
Electric Motor	1.1	1.4	1.6	2.0kW	2.2kW	1.8kW	1.8kW
Voltage	240	240	240	240	240	240	240
Outlet	10amp	10amp	10amp	10amp	15amp	10amp	10amp
Pump Head	Alum.um	Aluminium	Brass	Brass	Brass	Brass	Brass
Hose Storage	x	Winder	Winder	Reel	Reel	x	Reel
Hose Length	6m	8m	8m	12m	12m	15m	15m
Detergent	✓ Bottle	✓ Bottle	✓ Injection	✓ Tank	✓ Tank	✓ Tank	✓ Tank
Weight	11kg	13kg	13kg	22kg	25kg		
List	\$399 B	\$poa	\$585 B	\$979 C	\$poa	\$poa	\$1,639 C

INDUSTRIAL "K250 SERIES" 1400 Rpm

Designed from the ground up by Comet Italy in 2012. The new K250 provides industrial users top performance, high efficiency and long life. Suits users who need to run their machine for extended periods.



Pump

- Comet Italian 3 piston plunger pump with built in unloader (LW-K)
- Pump features brass head, ceramic pistons and conrods in an extra strong alloy for longer life
- Pump is self-priming with "Easy Start" device guarantees motor will start in all conditions

Motor

- 4 pole (1400rpm) electric motor, oversized for longer life
- Operates both vertically and horizontally
- Electrical Outlet - see matrix
- **TOTAL STOP** automatically shuts down the pressure washer down when the gun is closed
- Thermal motor protection in case of overheating, with manual restart

General features:

- Hose Reel with 15m of hose, gun with fixed jet and low pressure device
- Turbo Nozzle with lance included as a launch special
- Sturdy and reliable structure with tubular frame
- Sturdy injection-moulded plastic casing
- Practical to use in both vertical and horizontal operating position
- Practical housing for spray gun and lance
- Handle with supports for power supply cord and delivery hose
- Easy maintenance thanks to removable front casing
- Large wheels (Ø220mm) for easy movement over steps and rough terrain
- Removable detergent tank (3.5l) with externally visible level
- Detergent adjustment with filter
- Low-pressure detergent suctioning with adjustment
- Pressure gauge

Accessories included:

- Hose Reel with 15m of hose
- Gun/lance with Fan Nozzle and low pressure device
- Turbo Nozzle with lance included as a launch special



Supplied ready to go



1400 Rpm ELECTRIC					
Model	No Hose Reel		With Hose Reel		
	K250 9/120C	K250 10/150C	K250 9/120E	K250 10/150E	K250 13/190E
Pressure	1600	2000	1600	2000	2750
Flow	9	10	9	10	13
Electric Motor	2.0kW	2.2kW	2.0kW	2.2kW	5.2kW
Voltage	240	240	240	240	415
Outlet	10amp	15amp	10amp	15amp	na
Pump	Plunger Pump with Brass Head		Plunger Pump with Brass Head		
Hose Reel	x		✓		
Hose Length	15m		15m		
Detergent	Low Pressure on lance		Low Pressure on lance		
Weight	34kg	36kg	37kg	39kg	44kg
List	\$poa	\$poa	\$1,666 C	\$1,999 C	\$poa

Accessories		
	Gun & Lance \$poa	
	Lance c/w Turbo Nozzle \$poa	
LW-K Plunger Pump \$poa	Hose Reel \$poa	15m Hose \$poa

Electric Pressure Cleaners

Specialty Industrial Models



SLOW SPEED ELECTRIC

Spot

Professional IN PLACE systems where your machine needs to be wall mounted for security or safety. Built with a Nicolini slow speed electric motor, Interpump pump, stainless frame/cover & wall mounting brackets.

Features:

- Water proof 24V control panel
- Delayed total stop (after 30 minutes)
- Low Pressure detergent suction



MODEL	Psi	Flow	Motor	Power	Speed	List
K250 9/120Static	2030	9	2.2kW	240V	1440	\$1,999
SPOT 10/12	1740	10	3 HP	240V	1440	\$poa
SPOT 15/15	2175	15	5.5HP	415V	1440	\$poa
SPOT 15/21	2175	21	7.5HP	415V	1440	\$poa
SPOT 20/15	2900	15	7.5HP	415V	1440	\$poa
SPOT 20/21	2900	21	10HP	415V	1440	\$poa
SPOTDUO20/15	2900 X2	15 X2	7.5 X2	415V	1440	\$poa

Optional Hot Water seal kit where inlet water is warm.
Optional Remote switch available



Typhoon

Local machines built to your specific needs. Built with a Nicolini double bearing electric motor, Comet pump and galvanised frame. Machines built with pure grunt and no electronics..

Features:

- Nicolini slow speed, 2 bearing, double flange motor
- Comet pump
- Optional water feed tank in stainless
- Galvanised roll frame with provision for:
 - Hose Reel
 - Removable wheels



HD501815

MODEL	Psi	Flow	Motor	Power	Speed	Weight	List
HD151122	1500	15	2.2kW	415V	1440		\$poa
HD301555	3000	15	5.5kW	415V	1440		\$poa
HD302175	3000	21	7.5kW	415V	1440		\$poa
HD402110	4000	21	10.8Kw	415V	1440		\$poa
HD501815	5000	18	15kW	415V	1440		\$poa
HD302610	3000	26	11kW	415V	1440		\$poa
HD502218	5000	22	18.5kW	415V	1440		\$poa
HD721315	7200	13	15kW	415V	1440		\$poa



HD301555 with optional Water header tank

SLOW SPEED ELECTRIC

K Steel

A new series designed especially for BE in NZ. Our goal was to offer an industrial spec. unit at a reasonable price. Simply the best motor / pump group available for each performance level. Costs a bit more, but ideal for the heavy duty professional user, i.e. car wash plant

Features:

- Comet Premium Pump
- Slow speed 1400 Rpm electric motor
- External Unloader
- Delayed Total Stop c/w time delay
- Two oil sight glasses



Motor/Pump Group also available for custom builds



MODEL	Psi	Flow	Motor	Power	Pump	Kg	List
K803*	1740	11	2.2kW	240V 15	ZW	62	\$1,991B
K701	1595	12	2.2kW	240V 15	RW	62	\$2,448B
K801 😊	3335	15	7.3kW	415V	RW	70	\$2,999B
K901	2610	21	7.5kW	415V	RW	71	\$2,413B

* with built in unloader

COMETA

Ideal for those looking for a k Steel unit, but also require a water feed tank. This can be needed for higher flow machines, or where the tap water pressure is very low.

Features:

- Interpump Pump
- Water feed tank in stainless(5 or 15 litres)
- Slow speed 1400 Rpm electric motor
- Stainless AISI304 frame and cover
- External Unloader
- Waterproof control panel with Delayed Total Stop
- Detergent injection at high pressure



MODEL	Psi	Flow	Motor	Power	Pump	Weight	List
COMETA 20/15	2900	15	7.5kW	415V	IP	81	\$poa
COMETA 20/21	2900	21	10kW	415V	IP		\$poa
COMETA 20/30	2900	30	15kW	415V	IP		\$poa

AR Static



A tough, portable and compact unit ideal where you need a heavy duty unit, but need portability or to save space. **Popular with builders who need to haul a machine up multi story buildings and ladders or scaffolding**

Features:

- Triplex pump with ceramic plungers
- Automatic by-pass valve
- Pressure gauge
- Pressure adjustment
- Built-in detergent suction
- Motor thermal protector
- Power supply cord length 5m
- Mesh Water filter - Optional large filter kit available
- Detergent tank only for 610 mod.
- H.P. soft type hose gun and lance
- Adjustable high/low pressure and fan/pencil jet spray head
- Also ideal for small Hydrostatic Pipe Testing units

	AR STATIC			
Model	213 610	213 620	213 630	213 650
Pressure	1900	1900	1750	2200
Flow	8.3	8.0	10	8.0
Electric Motor	2.2kw	2.6kw	2.6kw	3.0kw
Voltage	240 Volt	240 Volt	240 Volt	240 Volt
Outlet	10amp (fitted)	10amp (not fitted)	15amp (not fitted)	15amp (not fitted)
Motor Speed	2800 rpm	2800 rpm	1400 rpm	2800 rpm
Pump Type	Plunger	Plunger	Plunger	Plunger
Pump Head	Aluminium Triplex	Aluminium Triplex	Brass Head	Brass Head
Detergent Tank	✓	x	x	x
Weight	18kg	20kg	21kg	21kg
Dimensions	L35xW22xH24	L39xW24xH23	L39xW24xH23	L39xW24xH23
List	\$723B	\$poa	\$949B	\$poa

FIRE HOT BOX SERIES

Why use a Hot Box?

Cold water pressure cleaners are not designed to pump hot water.

A Hot Box is ideal where:

- 1) You already have a cold water pressure cleaner and want to generate hot water
- 2) You prefer a Petrol driven pressure washer rather than an electric machine

Hot water is normally ideal where you need to remove oil, grease or any other heat reactive substance.

A Mobile Boiler burns diesel to heat the water. This is the same concept as our Hot Water machines.

The other option is to purchase a dedicated Hot Water machine

Features:

- Full stainless (AISI 430) frame & canopy with 4 pneumatic wheels
- Water temperature to 90°C
- C2 Double Coil (3/8" seamless)
- Stainless Fuel tank with 30 Litre capacity
- Includes 2 metre hose to connect to pressure cleaner (other sizes available)



SERIES	FIRE		
MODEL	FIRE A	FIRE C	VULKAN
Production Number	99000000	99000001	91290195
PERFORMANCE			
Water Pressure (Psi)	2900 Psi	5000 Psi	5000 Psi
Water Flow Rate - Min.	5 l/min.	5 l/min.	5 l/min.
Water Flow Rate - Max.	15 l/min.	25 l/min.	21 l/min.
Power Supply:			
To Fuel Pump	24 Volt	24 Volt	12 Volt
To Fan Motor	240 Volt	240 Volt	12 Volt
Burner:			
Coil - Type	C2 Seamless	C3 Seamless	C3 Seamless
Coil - Wall Thickness	2.8mm	2.8mm	3.0mm
Water Temperature	0°C→90°C		30→140°C
Fittings:			
Inlet			
Discharge			
Weight			
	103 Kg	70 Kg	
Dimensions			
	100 x 60 x 87cm	L71xW81xH91	
Full Specification Sheet			
Parts & Accessories			
List - Steel Coil	\$3,759 C	\$poa	\$poa
List - Stainless Coil	\$4,795 C	\$poa	\$poa



Attach a Mobile Boiler to our Cold water pressure cleaners



Upgrade to a vented Lance....needed when using Hot Water
145 40.0965.00 plus 125 85.300.107S